

HOMESURE

Mastertouch

दीवारों के
दीवाने



SUPERIOR
FINISH



RICH
COLOUR



LONG
LASTING



DISTEMPER

Mastertouch Distemper is water thinnable washable acrylic distemper suitable for interior walls. It helps to improve aesthetic appearance of surfaces.



FEATURES



Excellent workability



Easy to mix



Good opacity



Excellent adhesion



High Durability



Smooth brushability

SUBSTRATE

Distemper is suitable on new or previously painted masonry surfaces such as Primer surface and semi-permanent interior finishes.

COMPOSITION

- Pigment: Non-lead Pigments
- Extenders: Non-lead Fillers
- Binder: Styrene-Acrylic Emulsion
- Solvent: Water

SHELF LIFE

18 months from date of manufacturing in original tightly closed containers away from direct sunlight and excessive heat.

PRODUCT BENEFIT

High coverage.
 No added lead, Mercury, & Chromium Compound.
 Rich Aesthetic look.

TECHNICAL DATA	
PARAMETERS	SPECIFICATIONS
Nature	White Free Flowing Liquid
Dilution ratio	50% (with clean water)
Application	By Brush, Roller, & Spray
Coverage	60 – 80 Sq. Ft / Ltr / 2 Coat (may vary on surface condition)
Dryingtime	4-6 hrs.
Finish	Smooth & Matt
Stability	Stability of thinned Paint is 24 HRS

SUBSTRATE PREPARATION

- New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces. For repairing plaster surface use HomeSure WalliEX Ready Mix Plaster (for guideline refer HomeSure WalliEX Ready Mix Plaster TDS).
- Ensure the surface Should be completely free from dirt, dust, loose Paints, powdery residue, oil greases or any other contamination.
- Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Before application any crack and minor damages on surface should be repaired with HomeSure WalliEX Crack Filler (for guideline refer HomeSure WalliEX Crack Filler TDS).

MIXING

- Dilution: 50% with clean water.
- Ensure proper mixing of water in material before application.

PRIMER APPLICATION PROCESS

- Apply one coat of Interior Wall Primer with proper dilution and allow to dry for 4-6 hrs. (for guideline refer Interior primer TDS).
- Apply 2 Coat of HomeSure Wall Putty (for guideline refer HomeSure Wall Putty TDS). Ensure surface smoothness and levelling by sanding with sandpaper 180 and wipe clean.
- Apply one coat of Interior Wall Primer with proper dilution and allow to dry for 4-6 hrs. before topcoat application.
- Application can be done by using brush, roller, spray.

DISTEMPER APPLICATION PROCESS

- On primer application, apply two coats of Distemper with 50% water dilution.
- Take 4-6 hr drying time between two coats.
- Application can be done by using brush, roller, spray.

USAGE PRECAUTIONS

- Do not alter water addition than recommended level.
- For better performance two coat application is required.
- Distemper contains non-toxic material but still, it is important to wear a safety kit while mixing and handling Paint.

POST PAINTING CARE

- For the best performance of the paints, ensure proper washing and cleaning of algae and fungal growth.
- Washing should be done on regular intervals of six month.









INTERIOR PRIMER

Mastertouch Interior Primer is water thinnable wall primer specially featured with ease of application, fast drying, enhances the surface smoothness and provides good adhesion to the topcoat.



FEATURES

	Excellent workability		Good opacity		High Durability
	Easy to mix		Excellent adhesion		Smooth brushability

SUBSTRATE

Interior Primer is suitable on new or previously painted masonry surfaces such as brickwork, plaster, cement, rendering and semi-permanent interior finishes.

COMPOSITION

- Pigment: Non-lead Pigments
- Extenders: Non-lead Fillers
- Binder: Styrene-Acrylic Emulsion
- Solvent: Water

SHELF LIFE

18 months from date of manufacturing in original tightly closed containers away from direct sunlight and excessive heat.

PRODUCT BENEFIT

- High coverage for topcoat.
- Improved Paint adhesion.
- No added lead, Mercury, & Chromium Compound.

TECHNICAL DATA	
PARAMETERS	SPECIFICATIONS
Nature	White Free Flowing Liquid
Dilution ratio	50% (with clean water)
Application	By Brush, Roller, & Spray
Coverage	80-100 Sq. Ft / Ltr / Coat (may vary on surface condition)
Dryingtime	4-6 hrs.
Finish	Smooth & Matt
Stability	Stability of thinned Paint is 24 HRS

SUBSTRATE PREPARATION

- New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces. For repairing plaster surface use Walplast BuildWell Ready Mix Plaster (for guideline refer Walplast BuildWell Ready Mix Plaster TDS).
- Ensure the surface Should be completely free from dirt, dust, loose Paints, powdery residue, oil greases or any other contamination.
- Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Before application any crack and minor damages on surface should be repaired with Walplast HomeSure Crack Filler (for guideline refer Walplast HomeSure Crack Filler TDS).

MIXING

- Dilution: 50% with clean water.
- Ensure proper mixing of water in material before application.

PRIMER APPLICATION PROCESS

- Apply one coat of Interior Wall Primer with proper dilution and allow to dry for 4-6 hrs.
- Apply 2 Coat of Walplast HomeSure Wall Putty (for guideline refer Walplast HomeSure Wall Putty TDS). Ensure surface smoothness and levelling by sanding with sandpaper 180 and wipe clean.
- Apply one coat of Interior Wall Primer with proper dilution and allow to dry for 4-6 hrs. before topcoat application.
- Application can be done by using brush, roller, spray.

USAGE PRECAUTIONS

- Do not alter water addition than recommended level.
- Only one coat required.
- Interior primer contains non-toxic material but still, it is important to wear a safety kit while mixing and handling Paint.

POST PAINTING CARE

- For the best performance of the paints, ensure proper washing and cleaning of algae and fungal growth.
- Washing should be done on regular intervals of six month.



EXTERIOR PRIMER

Mastertouch Exterior Primer is water thinnable wall primer specially featured with ease of application, fast drying, enhances the surface smoothness and provides good adhesion to the topcoat.



FEATURES



Excellent workability



Economical



Superior Coverage



Easy to mix



Excellent adhesion



Smooth brushability

SUBSTRATE

Exterior Primer is suitable on new or previously painted masonry surfaces such as brickwork, plaster, cement, rendering and semi-permanent interior finishes.

COMPOSITION

- Pigment: Non-lead Pigments
- Extenders: Non-lead Fillers
- Binder: Styrene-Acrylic Emulsion
- Solvent: Water

SHELF LIFE

18 months from date of manufacturing in original tightly closed containers away from direct sunlight and excessive heat.

PRODUCT BENEFIT

- High coverage for topcoat.
- Prevent Peeling off of topcoat.
- No added lead, Mercury, & Chromium Compound.

TECHNICAL DATA	
PARAMETERS	SPECIFICATIONS
Nature	White Free Flowing Liquid
Dilution ratio	50% (with clean water)
Application	By Brush, Roller, & Spray
Coverage	80-100 Sq. Ft / Ltr / Coat (may vary on surface condition)
Dryingtime	4-6 hrs.
Finish	Smooth & Matt
Stability	Stability of thinned Paint is 24 HRS

SUBSTRATE PREPARATION

- New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces. For repairing plaster surface use HomeSure WallEX Ready Mix Plaster (for guideline refer HomeSure WallEX Ready Mix Plaster TDS).
- Ensure the surface Should be completely free from dirt, dust, loose Paints, powdery residue, oil greases or any other contamination.
- Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Before application any crack and minor damages on surface should be repaired with HomeSure WallEX Crack Filler (for guideline refer HomeSure WallEX Crack Filler TDS).

MIXING

- Dilution: 50% with clean water.
- Ensure proper mixing of water in material before application.

PRIMER APPLICATION PROCESS

- Apply one coat of Exterior Primer with proper dilution and allow to dry for 4-6 hrs. before topcoat application.
- Application can be done by using brush, roller, spray.

USAGE PRECAUTIONS

- Do not alter water addition than recommended level.
- Only one coat required.
- Exterior Primer contains non-toxic material but still, it is important to wear a safety kit while mixing and handling Paint.

POST PAINTING CARE

- For the best performance of the paints, ensure proper washing and cleaning of algae and fungal growth.
- Washing should be done on regular intervals of six month.

HOMESURE

Mastertouch

— दीवारों के दीवाने —



Walplast Products Pvt. Ltd. ISO 9001: 2015 Certified Company
Plot No A, 246, Cross Road Number 18, T.T.C. Industrial Area, MIDC
Industrial Area, Mahape, Navi Mumbai, Maharashtra-400 710.

Toll-Free No.: 1800 3000 6650

Email: customercare@walplast.com | Website: www.walplast.com

FOLLOW
US ON



SCAN FOR
MORE DETAILS

