

Front

W 6 X H 8.5 Inch

Pantone
2077C
HEX = #6E3FA3

Pantone
7687C
HEX = #1D428A

Pantone
710C
HEX = #E03E52

Pantone
715 C
HEX = #F68D2E



HOMESURE

SCRATCHEX

Texture Expert



Inner Left

W 6 X H 8.5 Inch

Pantone
7687C
HEX = #1D428A

Pantone
710C
HEX = #e03E52

Pantone
715 C
HEX = #f68d2e



**TOUGH
TEXTURE**



**EXCELLENT
COVERAGE**



**PLASTER
PROTECTION**



**WEATHER
PROTECTION**

HomeSure **ScratchEX** is formulated with modified acrylic emulsion and reinforced with quartz aggregates. Its **EX**pert formulation keeps it safe against the ill-effects of weather. It is highly recommended to be used on freshly plastered surfaces. We, the **EX**perts of texture, also assure that a totally new life can be given to old weather-beaten surfaces of your walls through our **EX**pertise.

Inner Right | W 6 X H 8.5 Inch

Pantone
7687C
HEX = #1D428A

Pantone
710C
HEX = #e03E52

Pantone
715 C
HEX = #f68d2e



Suitable for all types of exterior and interior walls to make them look more entertaining, interesting and appealing.

FEATURES

- ✓ **Hides cracks**
It hides crack in surface undulation and refines surface cracks.
- ✓ **Tough textured**
It's tough textured finish lasts long and ensures low maintenance.
- ✓ **Protection of plasters**
It protects the plastered wall from heavy rain and wind.

BENEFITS

- ✓ Good workability and high durability. It is highly compatible with plaster and concrete wall surface.
- ✓ Excellent resistance against the growth of algae and fungi on the wall.
- ✓ Provides best value for money.

Back

W 6 X H 8.5 Inch

Pantone
7687C
HEX = #1D428A

Pantone
710C
HEX = #e03E52

Pantone
715 C
HEX = #f68d2e



SUITABLE ON

- ✓ Cement Plaster
- ✓ Concrete
- ✓ Gypsum Board
- ✓ Masonry



SUGGESTED FINISHES



BRICKS



STONE




CUBE



HORIZONTAL



VERTICAL



RAINFALL

TECHNICAL DETAILS

Coverage: 2 – 2.5 Sq. Ft. / Kg / Coat

VOC: Less than 50 gm / Itr

Colour: Off White

Commodity: Acrylic texture

Available Package: 25 Kg & 30 Kg

Dry to recoat: 12 – 16 hrs

Thinning Recommended:

Dilute approx. 3 - 4 % if required

Thinner: Fresh Water

Touch Dry: 30 minutes (May vary as per temperature, humidity etc.)



Walplast Products Pvt. Ltd., ISO 9001: 2015 Certified Company
Plot No. A-246, TTC, Industrial Area, MIDC, Mahape,
Navi Mumbai, Maharashtra - 400701, India.

In case of a consumer complaint, please contact
Toll-Free No.: 1800 3000 6650
Email: customercare@walplast.com
Website: www.walplast.com

FOLLOW US ON



[/WALPLAST](https://www.walplast.com)

SCAN FOR
MORE
DETAILS

